

**Package Includes:**

Camera, IR Illuminator, Weatherproof Housing, Wall Mount Bracket

**Illuminator Features**

- High performance Infrared illumination
- 12 – 24 V AC/DC power input
- Long Life LED's, 5-Year Warranty
- Effective illumination ranges to 820 ft / 250m
- Patented "Even Illumination" both across a scene and depth-wise, eliminating all hotspots
- Beam patterns of: 10°, 45°, 60°

**Camera Features**

- Next Generation High Performance 1/3" Sony Super Dynamic HAD CCD
- 620 lines resolution
- Color by day, high sensitivity B&W by night (moving filter)
- 12VDC/24VAC/UTP power (2,000' distance)
- Built-in UTP transmitter (up to 6,000' distance)
- OSD, RS-485 option available



Model Numbers	Beam Angle	Wavelength	Illumination	Achievable Distance	Lens
IR18D2	10°	850nm	Semi-Covert	195 ft / 60 m	2.7-12mm
IR18D3	10°	850nm	Semi-Covert	195 ft / 60 m	3-8mm
IR18D5	10°	850nm	Semi-Covert	195 ft / 60 m	5-55mm
IR18D9	10°	850nm	Semi-Covert	195 ft / 60 m	9-90mm
IR48D2	45°	850nm	Semi-Covert	130 ft / 40 m	2.7-12mm
IR48D3	45°	850nm	Semi-Covert	130 ft / 40 m	3-8mm
IR48D5	45°	850nm	Semi-Covert	130 ft / 40 m	5-55mm
IR48D9	45°	850nm	Semi-Covert	130 ft / 40 m	9-90mm
IR68D2	60°	850nm	Semi-Covert	90 ft / 28 m	2.7-12mm
IR68D3	60°	850nm	Semi-Covert	90 ft / 28 m	3-8mm
IR68D5	60°	850nm	Semi-Covert	90 ft / 28 m	5-55mm
IR68D9	60°	850nm	Semi-Covert	90 ft / 28 m	9-90mm
IR218D2	10°	850nm	Semi-Covert	410 ft / 125 m	2.7-12mm
IR218D3	10°	850nm	Semi-Covert	410 ft / 125 m	3-8mm
IR218D5	10°	850nm	Semi-Covert	410 ft / 125 m	5-50mm
IR218D9	10°	850nm	Semi-Covert	410 ft / 125 m	9-90mm
IR248D2	45°	850nm	Semi-Covert	260 ft / 80 m	2.7-12mm
IR248D3	45°	850nm	Semi-Covert	260 ft / 80 m	3-8mm
IR248D5	45°	850nm	Semi-Covert	260 ft / 80 m	5-50mm
IR248D9	45°	850nm	Semi-Covert	260 ft / 80 m	9-90mm
IR268D2	60°	850nm	Semi-Covert	180 ft / 55 m	2.7-12mm
IR268D3	60°	850nm	Semi-Covert	180 ft / 55 m	3-8mm
IR268D5	60°	850nm	Semi-Covert	180 ft / 55 m	5-50mm
IR268D9	60°	850nm	Semi-Covert	180 ft / 55 m	9-90mm
IR318D2	10°	850nm	Semi-Covert	820 ft / 250 m	2.7-12mm
IR318D3	10°	850nm	Semi-Covert	820 ft / 250 m	3-8mm
IR318D5	10°	850nm	Semi-Covert	820 ft / 250 m	5-55mm
IR318D9	10°	850nm	Semi-Covert	820 ft / 250 m	9-90mm
IR348D2	45°	850nm	Semi-Covert	525 ft / 160 m	2.7-12mm
IR348D3	45°	850nm	Semi-Covert	525 ft / 160 m	3-8mm
IR348D5	45°	850nm	Semi-Covert	525 ft / 160 m	5-55mm
IR348D9	45°	850nm	Semi-Covert	525 ft / 160 m	9-90mm
IR368D2	60°	850nm	Semi-Covert	360 ft / 110 m	2.7-12mm
IR368D3	60°	850nm	Semi-Covert	360 ft / 110 m	3-8mm
IR368D5	60°	850nm	Semi-Covert	360 ft / 110 m	5-55mm
IR368D9	60°	850nm	Semi-Covert	360 ft / 110 m	9-90mm

Add "O" to end of model number for camera with OSD and RS-485