

Features

- 1/3" Color CCD
- 480 lines, 0.4 lux
- 70° field of view (3.6mm lens)
- Compact Size
- For indoor use
- 3-year warranty



Model	MDCE70	MDCE70X
Image Sensor	Color 1/3" CCD	
Field of View	70° Horizontal	
Lens	3.6mm	
Horizontal Resolution	480 TV Lines	
TV System	NTSC	PAL
Picture Elements (pixels)	512 (H) × 492(V)	512 (H) × 582(V)
Min. Illumination	0.4 lux	
Signal to Noise Ratio	More than 48dB	
Synchronizing System	Internal	
Electronic Iris	1/60~1/100,000 sec.	1/50~1/100,000 sec.
Video Output	1Vp-p 75ohm	
Power Requirement	12VDC ±10%	
Operating Current	110mA w/ regulated power in	
Operating Condition	+14 ~ 122°F (-10°C ~ +50°C)	
Measurements	ø3.9 × 2.4 inches (ø100mm × 60mm)	
Weight (Camera Only)	5.3 oz. (150g)	
Base Color	Black	
Optional Accessories	PS1250R - UL Approved 12V 500mA plug-in power supply (NTSC model only, US plug) EC60PV - 60' (18m) extension cable with BNC/Power connectors	

Specifications subject to change without notice

